

BLUE STRIPE® Shotgun Sticks



Utility Solutions offers both internal rod and external rod fixed length shotgun sticks.

BLUE STRIPE® Shotgun Sticks are manufactured from the highest electrical grade insulated fiberglass. Some of the features include:

- **Replaceable hanger hooks.**
- **Patented BLUE STRIPE® feature. When the stripe is facing up, the stainless steel hook will open downward minimizing accidental drops.**
- **Stainless steel operating hook.**
- **Multiple rod guides ensure smooth operation.**
- **High performance closed cell foam prevents water absorption (external rod models).**
- **Rubber Boot, spline end, socket adapter or quick connect options available.**

Standard model internal and external shotgun sticks utilize a full view side break hook (hook pivots in the horizontal plane in relation to the hook release trigger). Add the -BBH designation* to any internal rod shotgun stick to specify a bottom break hook (hook pivots in the vertical plane in relation to the hook release trigger).

Rugged and Versatile



Order an optional Hand Guard (USSA-HG1) to clearly mark minimum distance.

These products are patent protected under Patent number 6,875,917 and other patents pending. All BLUE STRIPE® Fiberglass Sticks are manufactured to meet industry standards including OSHA, ASTM and IEC as applicable.

Shotgun sticks are available with four standard end options:



EC - Rubber End Cap



FA - ½” Female Socket Adaptor



SE - Universal Spline End



QC - Quick Connect Hex Head

INTERNAL ROD	EXTERNAL ROD	SIZE		WEIGHT	BAG
with Rubber End Cap (EC)					
USSG-004-IREC	USSG-004-EREC	4' 6"	1.4 m	4 lb 4 oz	USSB-005
USSG-006-IREC	USSG-006-EREC	6' 6"	2 m	5 lb 3 oz	USSB-007
USSG-008-IREC	USSG-008-EREC	8' 8"	2.6 m	5 lb 14 oz	USSB-009
USSG-010-IREC	USSG-010-EREC	10' 6"	3.2 m	6 lb 13 oz	USSB-011
USSG-012-IREC	USSG-012-EREC	12' 6"	3.8 m	9 lb 8 oz	USSB-012
with Universal Spline End (SE)					
USSG-004-IRSE	USSG-004-ERSE	4' 6"	1.4 m	4 lb 4 oz	USSB-005
USSG-006-IRSE	USSG-006-ERSE	6' 6"	2 m	5 lb 3 oz	USSB-007
USSG-008-IRSE	USSG-008-ERSE	8' 8"	2.6 m	5 lb 14 oz	USSB-009
USSG-010-IRSE	USSG-010-ERSE	10' 6"	3.2 m	6 lb 13 oz	USSB-011
USSG-012-IRSE	USSG-012-ERSE	12' 6"	3.8 m	9 lb 8 oz	USSB-012
with Female ½” Socket Adaptor End (FA)					
USSG-004-IRFA	USSG-004-ERFA	4' 6"	1.4 m	4 lb 4 oz	USSB-005
USSG-006-IRFA	USSG-006-ERFA	6' 6"	2 m	5 lb 3 oz	USSB-007
USSG-008-IRFA	USSG-008-ERFA	8' 8"	2.6 m	5 lb 14 oz	USSB-009
USSG-010-IRFA	USSG-010-ERFA	10' 6"	3.2 m	6 lb 13 oz	USSB-011
USSG-012-IRFA	USSG-012-ERFA	12' 6"	3.8 m	9 lb 8 oz	USSB-012
with Quick Connect Hex Head End (QC)					
USSG-004-IRQC	USSG-004-ERQC	4' 6"	1.4 m	4 lb 4 oz	USSB-005
USSG-006-IRQC	USSG-006-ERQC	6' 6"	2 m	5 lb 3 oz	USSB-007
USSG-008-IRQC	USSG-008-ERQC	8' 8"	2.6 m	5 lb 14 oz	USSB-009
USSG-010-IRQC	USSG-010-ERQC	10' 6"	3.2 m	6 lb 13 oz	USSB-011
USSG-012-IRQC	USSG-012-ERQC	12' 6"	3.8 m	9 lb 8 oz	USSB-012

**Add -BBH for optional Bottom Break Hook*